

**AMENDMENTS TO THE CLAIMS:**

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. **(currently amended)** A process, comprising the steps of:  
feeding at least a single continuous web in a machine direction as a component member of a disposable wearing article being continuously manufactured,

feeding continuous elastic members toward at least one surface of said web while said continuous elastic members are oscillated in a cross direction relative to said machine direction, and  
attaching said continuous elastic members in a stretched state to said one surface in accordance with a desired layout, ~~said process further comprising the steps of:~~

feeding said web to a nip between a pair of press rolls substantially being in contact with each other and adapted to rotate in said machine direction around respective axes extending parallel to each other in said cross direction; and

feeding said elastic members from upstream of said pair of press rolls to the nip between said press rolls via at least one guiding mechanism ~~guide-means~~ adapted to oscillate said elastic members in said cross direction and attaching said elastic members to said web by means of an adhesive;

wherein each of said at least one guiding mechanism ~~guide-means~~ comprises:

a motor having a rotary shaft extending in a direction crossing said axes and adapted to repeat reversal of its rotational direction;

an arm connected directly with said rotary shaft and extending in a direction crossing said rotary shaft, said arm being formed on its distal end with a guiding element ~~guide-means~~ adapted

for passage of said elastic members, and said arm being adapted to swing around said rotary shaft as said rotary shaft rotates; and

at least one feed member located upstream of said rotary shaft as viewed in said machine direction and adapted to direct said elastic members toward said guiding element ~~guide means~~; and

wherein, in the course of running from said feed member to said pair of press rolls via said at least one guiding mechanism ~~guide means~~, said elastic members are attached to said web while said elastic members are oscillated in said cross direction by said arm connected directly with said rotary shaft so as to repeat reversal of its swinging direction;

said process further comprising arranging said axes of said press rolls horizontally, said rotary shaft of said motor vertically, and said arm to extend horizontally from said rotary shaft toward said nip between said press rolls.

2. **(currently amended)** The process according to [[Claim]] claim 1, further comprising using a servomotor as said motor.

3. **(currently amended)** The process according to [[Claim]] claim 2, further comprising controlling said servomotor on the basis of a running speed of at least said web in said machine direction and said layout desired for said elastic members.

4. **(currently amended)** The process according to ~~Claim 1~~ claim 2, wherein said arm is formed from a composite material comprising any one selected from the group consisting of carbon fiber, glass fiber, metallic fiber, synthetic fiber, semi-synthetic fiber and natural fiber and any one selected from the group consisting of thermoplastic synthetic resin and thermosetting synthetic resin.

5. (canceled)
6. **(currently amended)** The process according to [[Claim]] claim 1, wherein said elastic members are directed from said guiding element ~~guide means~~ to said nip between said pair of press rolls so that said elastic members are positioned in a plane tangential to said press rolls in a region in which said press rolls substantially contact each other.
7. **(currently amended)** The process according to [[Claim]] claim 5, wherein said elastic members extend from said feed member to said guiding element ~~guide means~~ at a deviation angle of 10° or less relative to a horizontal plane ~~defined by the parallel axes of said press rolls~~.
8. (canceled)
9. **(currently amended)** The apparatus according to ~~Claim 8~~ claim 15, wherein said motor is a servomotor.
10. **(currently amended)** The apparatus according to [[Claim]] claim 9, further comprising a controller, wherein said servomotor is electrically connected with the controller which is programmed to rotate said servomotor on the basis of a running speed of at least said web in said machine direction and said layout desired for said at least one elastic member.
11. **(currently amended)** The apparatus according to ~~Claim 8~~ claim 9, wherein said arm contains a composite material comprising any one selected from the group consisting of carbon fiber, glass fiber, metallic fiber, synthetic fiber, semi-synthetic fiber and natural fiber and any one selected from the group consisting of thermoplastic synthetic resin and thermosetting synthetic

resin.

12. (currently amended) The apparatus according to Claim-8 claim 15, wherein said axes of said press rolls extend horizontally in a horizontal plane, said rotary shaft of said motor extends vertically in a vertical direction, and said arm horizontally extends in said horizontal plane from said rotary shaft toward a nip between said press rolls.

13. (currently amended) The apparatus according to Claim-8 claim 15, wherein said arm extends substantially in a plane tangential to said press rolls in a region in which said press rolls substantially contact each other.

14. (currently amended) The apparatus according to Claim-8 claim 15, wherein said feed member and said guiding element are located so that said at least one elastic member extends from said feed member to said guiding element at a deviation angle of 10° or less relative to a horizontal plane ~~defined by the parallel to the~~ axes of said press rolls.

15. (currently amended) An apparatus for feeding at least a continuous web in a machine direction as a component member of disposable wearing articles being continuously manufactured, feeding at least one continuous elastic member toward at least one surface of said web while said at least one continuous elastic member is oscillated in a cross direction transverse to said machine direction, and attaching said at least one continuous elastic member in a stretched state to said one surface in accordance with a desired layout, said apparatus comprising:

a pair of press rolls substantially contacting each other, said press rolls being rotatable around respective axes extending in said cross direction so as to feed said web in said machine direction, and

a guiding mechanism located upstream of said press rolls as viewed in said machine direction to oscillate said at least one elastic member in said cross direction;

wherein said guiding mechanism comprises:

a motor which has a rotary shaft extending in a direction transverse to said axes and is adapted to repeatedly reverse a rotational direction of said rotary shaft;

an arm connected directly with said rotary shaft and longitudinally extending in a direction transverse to said rotary shaft, said arm being formed on a distal end thereof with a guiding element through which said at least one elastic member is passable, and said arm being adapted to swing around said rotary shaft as said rotary shaft rotates; and

at least one feed member located upstream of said rotary shaft as viewed in said machine direction and adapted to direct said at least one elastic member toward said guiding element;

~~The apparatus according to claim 8,~~ wherein an axis of said rotary shaft is stationary relative to the axes of said press rolls.

16. (previously presented) The process according to claim 1, further comprising maintaining an axis of said rotary shaft stationary relative to the axes of said press rolls while the elastic members are being fed and oscillated at the same time towards said nip.

17. (previously presented) The process according to claim 1, wherein said elastic members are attached to said web by means of the adhesive only in regions corresponding to leg openings of the disposable wearing article being manufactured;

said method further comprising

cutting the elastic members between said regions so that the cut elastic members do not extend across an entire width of the disposable wearing article being manufactured, and

attaching an absorbent core to said web, wherein portions of the cut elastic members that

have not been attached to said web contract to a relaxed state and are located near transverse edges of the absorbent core.

18. **(currently amended)** The process according to claim 1, further comprising controlling rotational oscillating movements of the arm of each said at least one guiding mechanism guide means such that ~~at least one of (i) the desired layout and (ii) a stretching ratio of the elastic members fed by one guiding mechanism guide means is different from that of the elastic members fed by the other guiding mechanism guide means.~~

19. **(previously presented)** The apparatus according to claim 8, wherein a rotational axis about which the arm swings coincides with a rotational axis of said rotary shaft.

20-21. **(canceled)**

22. **(new)** The apparatus according to claim 11, wherein said arm has a full weight of 96 to 121 g, a specific gravity of 1.5 to 1.8, a bending modulus of 98 to 201 GPa, and a full length of 250 to 350 mm, thereby allowing the servomotor to repeatedly swing said arm at a maximum angular acceleration of 15,000 rad/sec<sup>2</sup>.

23. **(new)** The process according to claim 4, wherein said arm has a full weight of 96 to 121 g, a specific gravity of 1.5 to 1.8, a bending modulus of 98 to 201 GPa, and a full length of 250 to 350 mm, thereby allowing the servomotor to repeatedly swing said arm at a maximum angular acceleration of 15,000 rad/sec<sup>2</sup>.